



DATE: September 24, 2021

QUOTE # [REDACTED]

**WILLIAMSON COUNTY FLEET**

**Jeffrey Kell**  
512.917.3277

3151 SE INNER LOOP STE B  
GEORGETOWN, TEXAS 78626-6343

**One (1) New Caterpillar Inc Model: RM500B Paving and Compaction with all standard equipment in addition to the additional specifications listed below:**

**STOCK NUMBER:** [REDACTED]

SALE PRICE	\$734,027.00
<b>TOTAL PRICE</b>	<b>\$734,027.00</b>
<hr/>	
<b>SUB TOTAL</b>	<b>\$734,027.00</b>
<b>TOTAL SOURCEWELL PURCHASE PRICE</b>	<b>\$734,027.00</b>

List Price	\$1,000,969.00
Sourcewell discount 20%	(\$200,194.00)
Adjusted Sales price	\$800,775.00
Dealer Prep	\$4,500.00
Delivery	\$1,050.00
Holt Cat Discount	(\$72,289.00)
<b>Total Sourcewell Purchase price</b>	<b>\$734,027.00</b>

Delivery – 1<sup>st</sup> quarter 2022

**WARRANTY**

**Standard Warranty: 12 Month/Unlimited Hours Total Machine**

**Extend Warranty  
Powertrain,  
Hydraulics, and  
Techology**

**48 months or 2,500 hours - \$11,250.00**

**60 months or 3,000 hours - \$15,807.00**

Sourcewell #32119-CAT

**NOTES**

Beacon  
Includes 12 month Field Service no charge  
Pricing good until 12/31/2021 and delivery in 2022

**MACHINE SPECIFICATIONS****STOCK NUMBER:** [REDACTED]

DESCRIPTION	REF.#
MACHINE, RM500B COMMON	593-7116
LANE 3 ORDER	0P-9003
ENGINE, CAT C15	560-3149
PLUG, NO WATER PUMP OPTION	423-8795
<b>CAB</b>	377-0276
MIRRORS	377-6138
ROPS	433-4304
PRODUCT LINK, CELLULAR PL641	490-1774
TIRES, 725/70-25 TI 16PR L-4	379-3203
TIRES, 23.1"-26" GY 16PR LS-2	379-3209
ROTOR, 16" UNIVERSAL	287-1724
SHEAR DISK	151-7256
COMMISSIONING, NOT NEEDED	0P-2587
OIL, HYDRAULIC STANDARD	384-9589
INSTRUCTIONS, ANSI	384-9598
<b>DUAL PUMPS, WATER AND EMULSION</b>	433-5808
LIGHTS, ROADING	382-9531
LIGHT, WARNING BEACON	234-0310
COUNTERWEIGHT, RECLAMATION	287-3675
PACK, DOMESTIC TRUCK	0P-0210
PLUG, NO EMULSION PUMP OPTION	438-2255
RM500B ROTARY MIXER	593-7117
<b>SPRAY, WATER</b>	379-8944
<b>SPRAY, EMULSION (VANE PUMP)</b>	379-9700

**STANDARD EQUIPMENT****POWERTRAIN**

CAT C-15 diesel, ACERT, 6-cylinder turbocharged engine, 540 HP (403 kW)  
 Air cleaner, dry-type dual element with precleaner  
 Air-to-air after cooler (ATAAC)  
 Belt, serpentine, automatic tensioner  
 Demand fan  
 Fuel filter / water separator  
 Fuel priming pump, electric  
 Ground level engine shutdown  
 Propel system - All Wheel Drive  
 4 propel pumps, 4 propel motors

Electronically managed differential  
 Two-speed, axial piston hydraulic motors (4) with 2F/2R speeds  
 Heavy-duty, wheel planetary gearsets  
 Brakes, oil-bath, sealed at each wheel  
 Secondary parking brake switch  
 Engine load / speed control, automatic  
 Steering, four modes:  
 - front  
 - crab  
 - coordinated  
 - rear

## **ELECTRICAL**

Alarm, back-up  
Alternator, 150-amp  
Batteries, two maintenance free,  
1365 CCA each  
Horn, warning (front & rear)  
Lighting system

- 6 halogen,  
- adjustable floodlights  
(2 front, 2 rear, 1 facing rotor  
chamber door)  
Starting and charging system, 24-volt  
Product Link Ready

## **OPERATOR ENVIRONMENT**

Access ladder, left and right side  
Electric heated seats  
Touch screen display showing:  
- engine speed, rpm  
- engine temperature  
- hydraulic temperature  
- engine coolant, fuel level  
- rotor transmission temperature  
- engine oil, pressure  
- voltage indicator  
- front and rear door aperture  
- liquid additive controls

Platform handrails / guardrails  
Electronic mini wheel steer  
Multi function drive lever  
Adjustable arm rest  
Seat, suspension, 90 degree L/R rotating  
Seat belt, retractable, 3" (76 mm) wide  
Sliding operator station, full width Hyd  
Warning system, action light and horn  
Air conditioner with heater  
Audio ready system with speakers  
Positive pressure cabin

## **APPLICATION SPECIFIC COMPONENTS**

Axle, heavy-duty  
Depth control, automatic  
Dual sealed chain cases  
Self-lubricating rotor end bearings

Single strand drive chains  
Maintenance free U-joint drive shafts  
Transmission, 3-speed, powershift

## **FLUIDS**

50% Extended Life Coolant for freeze

protection to -29F (-34C)

## **OTHER STANDARD EQUIPMENT**

Doors, service access, hinged  
Ecology drains  
Electrical system  
Circuit breaker panel and disconnect  
switch  
Machine diagnostic connector (CAT ET)  
Charging receptacle for emergency  
start, ground level  
Engine enclosure  
Fuel tank with sediment drain,  
279 gal (1056 L)  
Guard, (crankcase and powertrain)  
Hitch, front bumper with pin  
Hydraulic system  
Filters, grouped, ground level service

Oil cooler  
Pressure test ports, quick-connect  
Rotor chamber doors, F & R, hyd with  
electronic position indicators  
Rotor hood lock-up device  
Rotor hood side access doors  
Rotor transmission oil cooler  
Sight gauges (engine coolant,  
hydraulic oil level, rotor bearing  
lube reservoir)  
S.O.S. sampling ports  
Steering guide chains (2)  
Transport tie-down and lift ports  
Vandalism protection caplocks  
Variable volume mixing chamber

